

スタンダード ブラインドリベット

NSA

丸 頭




【リベットボディ】


アルミニウム
(A 5154)

【マンドレル】

スチール
(炭素鋼)



くかしまり図>



リベット径 Dφ (mm)	下穴径 φ (mm)	品 番	適正かしめ板厚 (mm)	寸 法 (mm)					参考強度 (kN)		小箱入数 (本)	梱包単位 (箱)				
				L	Hφ	T	Wφ	F	引張強度	せん断強度						
2.4	2.5～2.6	NSA3-2	1.0～3.2	5.6	4.8	0.9	1.45	35	0.70	0.48	1,000	20				
		NSA3-3	1.6～4.8	7.6												
		NSA3-4	3.2～6.4	9.1												
3.2	3.3～3.4	NSA4-1	1.0～1.6	4.8	6.4	1.1	1.8	38	1.35	0.96	1,000	20				
		NSA4-2	1.0～3.2	6.5												
		NSA4-3	1.6～4.8	8.2												
		NSA4-4	3.2～6.4	9.9												
		NSA4-5	4.8～8.0	11.6			1.9	53	1.34	0.87	10					
		NSA4-6	6.4～9.5	13.3												
		NSA4-8	9.5～12.7	16.7												
		NSA4-10	12.7～15.9	19.0												
NSA4-12	15.9～19.1	23.0														
4.0	4.1～4.2	NSA5-2	1.2～3.2	7.2	8.0	1.3	2.24	42	2.20	1.55	1,000	10				
		NSA5-3	1.6～4.8	8.9												
		NSA5-4	3.2～6.4	10.5												
		NSA5-5	4.8～8.0	12.2												
		NSA5-6	6.4～9.5	13.9			48									
		NSA5-8	9.5～12.7	17.2												
		NSA5-10	12.7～15.9	19.7												
NSA5-12	15.9～19.1	23.0	55													
4.8	4.9～5.0	NSA6-2	1.6～3.2	7.6	9.6	1.9	2.64	48	3.30	2.20	1,000	5				
		NSA6-3	1.6～4.8	9.3												
		NSA6-4	3.2～6.4	11.0												
		NSA6-5	4.8～8.0	12.8												
		NSA6-6	6.4～9.5	14.5			2.64	56			500					
		NSA6-8	9.5～12.7	17.9												
		NSA6-10	12.7～15.9	21.3												
		NSA6-12	15.9～19.1	24.8												
		NSA6-14	19.1～22.3	28.2												
NSA6-16	22.3～25.4	29.7	60													
			66													
6.4	6.5～6.6	NSA8-2	1.6～3.2	9.2	12.8	2.4	3.83	60	5.30	3.40		500	5			
		NSA8-4	3.2～6.4	12.4												
		NSA8-6	6.4～9.5	15.6												
		NSA8-8	9.5～12.7	18.9												
		NSA8-10	12.7～15.9	22.1			3.83	70								
		NSA8-12	15.9～19.1	25.4												
		NSA8-14	19.1～22.3	28.6												

NSA-T 強化タイプ

丸 頭

新 製 品

◎リベットボディを厚肉化することで強度を大きく向上しました。

リベット径 Dφ (mm)	下穴径 φ (mm)	品 番	適正かしめ板厚 (mm)	寸 法 (mm)					参考強度 (kN)		小箱入数 (本)	梱包単位 (箱)
				L	Hφ	T	Wφ	F	引張強度	せん断強度		
6.0	6.1~6.2	※NSA6032T	1.6~3.2	8.0	11.0	1.9	2.85	48	5.25	3.73	1,000	5
		※NSA6048T	3.2~4.8	10.0								
		※NSA6064T	4.8~6.4	12.0								

※印は受注生産品です。

新製品



A-FELIX 株式会社

〒224-0003 横浜市都筑区中川中央1-4-6 フォーレスト・センタービル 3F TEL 045-532-6900 FAX 045-532-6909